INTACT WATER

Intact Compact

360° Anti-Leak Double Backwash Outdoor Water Filter

Water flow rate up to

4000 L/hr

Remain your water pressure

INDUSTRIAL DESIGN REG. NO. MY-23-00939-0101

ASEAN RECORDS

Utilizing Ultra Filtration Technology with a filtration precision of up to 0.01 micron, it ensures 100% clean water and provides double protection.

360° ANTI-LEAK DOUBLE BACKWASH SYSTEM

(INDUSTRIAL DESIGN: MY 23-00939-0101)

1. Ensure the valve arrow points to "Filter" Mode.
2. Open the bottom tap and flush until the water runs clear, then close it.
3. Switch the valve to "Backwash" Mode.
4. Open the upper tap and flush until the water runs clear.
5. Return to "Filter" Mode and wait for the upper tap's water flow to stop.
6. Lastly, close the upper water tap.

STAINLESS STEEL HIGHER GRADE FULLY SUS 304

Zero Membrane Complaint Rate

- Corrosion Resistance
- Invisible Pipe
- Heat Resistance
- Strong & Durable
- Chemical Resisitance
- Lifetime Warranty Against Manufacturing Defects

DOUBLE BACKWASH MULTI VALVE EASY TO MAINTENANCE

UPGRADED CASING

Dual-layer Protection

CONTRACTION DUAL-LAYER
Durable casing with a contraction-based design for enhanced strength and durability.

ENHANCED FILTRATION
The filter is securely fixed inside the lid, delivering cleaner and more efficient water filtration.

360° ANTI LEAK SYSTEM
Leak-proof mechanism ensures no unfiltered water escapes.

Do You Know

WHAT DOES 0.01 MICRON FILTRATION MEAN?

BACTERIAL	FINE IMPURITIES	ORGANIC MATTER	DECAY MATTER
(0.02 - 0.35 micron)	(0.02 - 0.09 micron)	(0.03 - 3 micron)	(0.22 - 4 micron)

With a filtration capability of 0.01 micron, it effectively removes contaminants — ensuring clean, pure, and safe water.

INTACT WATER

PVDF ULTRA FILTRATION OF INTACT COMPACT

The PVDF Ultra Filtration Membrane System features ultrafine filtration with a pore size of **0.01 micron**, effectively removing impurities such as dirt, rust, sediment, and harmful bacteria.

Specially engineered for hot climate, the PVDF membrane performs efficiently under high temperatures, ensuring reliable operation even in extreme conditions.

REINFORCED FILTER ELEMENT
Intact's reinforced design delivers superior durability, capable of withstanding the weight of an adult man — showcasing exceptional strength and resilience.

PVDF material also boasts excellent resistance to most acids and alkaline water supply conditions, making it ideal for long-term performance in diverse environments.

INTACT COMPACT FILTER ELEMENT

- SOLID-MESH SURFACE
- HIGH FLOW RATE
- HEAT RESISTANT BLACK COVER
- 100% NON TOXIC ABS MATERIAL
- 300 CAVITIES
- SGS CERTIFIED
- EXTRA DURABLE
- 3-YEARS WARRANTY ON 360° FILTER ELEMENT

HIGH FLOW RATE

UNIQUE ONE AND ONLY

- PVDF MEMBRANE
- 360° ANTI LEAK DESIGN
- 300 CAVITIES
- NON-TOXIC ABS MATERIALS

INTACT WATER

LONG DURABILITY

EFFECTIVE FOR SOIL, SEDIMENT, BACTERIAL, AND OTHER HARMFUL MICROORGANISMS

- BACTERIAL
- SOIL
- SEDIMENT
- HARMFUL MICROORGANISMS

0.01 MICRON ULTRA-FINE MEMBRANE | **38%** ↑ HIGH FLOW | **50%** ↑ LONGER-LASTING MEMBRANE

Engineered to maintain **consistent flow rates** even under **high water pressure** (up to 8 bar), ensuring long-term durability with reliable filtration performance.

ENSURE YOU HAVE CLEAN WATER FOR

- BRUSHING
- LAUNDRY
- CLEANING
- BATHING
- COOKING
- WASHING

INTACT COMPACT

OPERATION INSTRUCTION MANUAL

INTACT COMPACT

Purifies your entire home's water — clean and safe for every tap, from showers to kitchen use. Enjoy peace of mind with smart, whole-house protection powered by advanced filtration technology.

INTACT WATER

WE CARE FOR EVERY DROP

Enjoy Clean, Safe Water With Intact Compact

LIFETIME WARRANTY AGAINST MANUFACTURING DEFECTS

LIFETIME WARRANTY
Against Manufacturing Defects

3 YEARS WARRANTY ON 360° ANTI-LEAK ELEMENT

3 YEARS WARRANTY
On 360° Anti-Leak Element

PRODUCT SPECIFICATIONS

PRODUCT MODEL:	PRODUCT FLOW RATE:	BODY MATERIAL:	INPUT & OUTPUT SIZE:
Intact Compact	4000L/HR	SUS 304 (Matt)	6"
MODEL CODE:	**TYPE OF FILTRATION:**	**BODY WARRANTY:**	**OTHER WARRANTY:**
UF-OD-COMPACT-PVDF	In Side Out Filtration	Lifetime Warranty Against Manufacturing Defects	360° Valve: 2 Years Piping: 2 Years Accessory: 1 Year
PACKAGING DIMENSION:	**BODY DIMENSION:**		
L:650mm x W:220mm x H:216mm	L:607.5mm x W:142mm		

PRODUCT MODEL:	PRODUCT FLOW RATE:	ELEMENT MATERIAL:	ELEMENT CAVITIES:
Intact Compact 360° Element	4000L/HR	PVDF	300
MODEL CODE:	**TYPE OF FILTRATION:**	**WARRANTY:**	
UF-F-COMPACT-PVDF	In Side Out Filtration	3 Years On 360° Element	
PACKAGING DIMENSION:	**BODY DIMENSION:**	**RATED WATER PRESSURE:**	
L:650mm x W:220mm x D:216mm	L:450mm x W:115mm	7-8 Bar	